Safety Data Sheet



Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name Low Density Polyethylene

Synonyms Ethene polymer; Ethylene Homopolymer; LDPE; Polyethylene

Product Grades EN1817AS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) Plastic film, laminating, molding, coating.

1.3 Details of the supplier of the safety data sheet

Manufacturer Westlake Polymers LLC

2801 Post Oak Blvd. Houston, TX 77056 United States www.westlake.com

Telephone (General) 713-960-9111

1.4 Emergency telephone number

800-424-9300 - CHEMTREC

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP • Not classified
DSD/DPD • Not classified

2.2 Label Elements

CLP Hazard
Statements

• No label element(s) required

DSD/DPD Risk phrases • No label element(s) required

2.3 Other Hazards

• May form combustible dust concentrations in air.

According to Regulation (EC) No. 1272/2008 (CLP) this material is not considered hazardous.

• May form combustible dust concentrations in air.

According to European Directive 1999/45/EC this material is not considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

Not classified

2.2 Label elements

OSHA HCS 2012

Hazard statements

No label element(s) required

2.3 Other hazards

OSHA HCS 2012

 As shipped, product is not hazardous. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is not considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

Not classified

2.2 Label elements

WHMIS

• No label element(s) required.

2.3 Other hazards

WHMIS

 May form combustible dust concentrations in air.
 In Canada, the product mentioned above is not considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Composition			
Chemical Name	Identifiers (CAS)	%	
Polyethylene	9002-88-4	>97	
Slip and/or Antioxidants	Proprietary	<1–0	
Diatomaceous Earth* or Talc**	68855-54-9 or 14807-96-6	<2.0 – 0	

^{*} contains crystalline silica CAS #s 14464-46-1 & 14808-60-7

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

• IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

• For thermal burns, flush or submerge effected area in cold water to dissipate heat. Cover with clean bandage material. Do not peel material from skin. Get medical attention. For contact at ambient temperatures, wash with soap and water.

Eye

• If dust or molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention immediately.

Ingestion

• First aid is not expected to be necessary if material is used under ordinary conditions and as recommended.

4.2 Most important symptoms and effects, both acute and delayed

^{**} contains < 1% quartz or crystalline silica

• Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

• Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media

• Water fog, dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media

· None known.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

• Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Hazardous Combustion Products

• Carbon dioxide, carbon monoxide, formaldehyde, acetaldehyde, irritating smoke.

5.3 Advice for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA).
 Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

• Do not walk through spilled material. Do not breathe dust. Avoid contact with skin and eyes. Wear appropriate personal protective equipment, avoid direct contact.

Emergency Procedures

Contain spill and monitor for excessive dust accumulation. Avoid unnecessary
personnel and equipment traffic in the spill area. Ventilate closed spaces before
entering.

6.2 Environmental precautions

No special environmental precautions necessary.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Avoid generating dust.
- Use clean nonsparking tools to collect material.
- Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 -Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Avoid contact with molten material; do not breathe fumes, vapors, dust or sprays from molten or burning material. When processing at > 600°F (315°C), consider use of a respirator to avoid breathing decomposition products.
- Do not use in areas without adequate ventilation. Minimize dust generation and accumulation.
 Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
 Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Use appropriate Personal Protective Equipment (PPE) Avoid contact with skin and eyes. Do not
breathe dust. Wash thoroughly with soap and water after handling and before eating, drinking, or
using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

• Keep container closed and in ventilated area, away from ignition sources, heat, open flames, and direct sunlight. Do not store with incompatible materials.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses

7.4 Other Information

For prevention of fire and explosion, keep from contact with incompatible materials. Minimize
dust generation and accumulation. Because product may accumulate a static charge, use
proper bonding and/or grounding procedures prior to transfer. In the United States of America,
refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions from the
Manufacturing, Processing, and Handling of Combustible Particulate Solids, 2006 edition."

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines				
	Result ACGIH		NIOSH	
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
Talc (14807-96-6)		2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	2 mg/m3 TWA (containing no Asbestos and <1% Quartz, respirable dust)	

8.2 Exposure controls

Engineering Measures/Controls

Good general ventilation (typically 10 air changes per hour) should be used.
 Ventilation rates should be matched to conditions. Supplementary local exhaust
 ventilation, closed systems, or respiratory and eye protection may be needed in
 special circumstances; such as poorly ventilated spaces, very hot processing,
 evaporation of liquids from large surfaces, spraying of mists, mechanical generation
 of dusts, drying of solids, etc.

Personal Protective Equipment

Respiratory

For limited exposure use an N95 dust mask. For prolonged exposure use an air-purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

· Wear safety goggles.

Hands

Wear thermally resistant gloves and long sleeves when handling molten product.

Skin/Body

Wear long sleeves and/or protective coveralls.

Environmental Exposure Controls

Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15 minute exposures TWA = Time Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description				
Physical Form	Solid	Appearance/Description	A translucent to whitish solid with an odorless to mild odor.	
Color	Translucent to whitish.	Odor	Odorless to mild.	
Odor Threshold	NDA			
General Properties				
Boiling Point	NDA	Melting Point	100 to 120 C(212 to 248 F)	
Decomposition Temperature	>300 C (573 F) (estimated)	рН	NDA	
Specific Gravity/Relative Density	0.901 to 0.935 Water=1	Water Solubility	Negligible.	
Viscosity	NDA	Explosive Properties	Not Explosive.	
Oxidizing Properties:	Not an oxidizer.			
Volatility				
Vapor Pressure	NDA	Vapor Density	NDA	
Evaporation Rate	NDA			
Flammability	•	-	•	
Flash Point	>343 C(649.4 F) (estimated)	UEL NDA		
LEL	NDA	Autoignition	NDA	
Flammability (solid, gas)	Not Flammable.			
Environmental				
Octanol/Water Partition coefficient	NDA			

9.2 Other Information

· No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

• No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

• Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

· Hazardous polymerization not indicated.

10.4 Conditions to avoid

• Heat, sparks, open flame.

10.5 Incompatible materials

• Strong oxidizing agents, fluorine.

10.6 Hazardous decomposition products

No data available

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data		
Cristobalite (< 1.4%)	14464-46-1	Multi-dose Toxicity: Inhalation-Mouse TCLo • 70 mg/m³ 5 Hour(s) 12 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Other changes; Inhalation-Mouse TCLo • 43 mg/m³ 5 Hour(s) 9 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Pleural effusion; Lungs, Thorax, or Respiration:Other changes; Inhalation-Mouse TCLo • 70 mg/m³ 5 Hour(s) 12 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Other changes; Inhalation-Mouse TCLo • 43 mg/m³ 5 Hour(s) 9 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Pleural effusion; Lungs, Thorax, or Respiration:Other changes		
Quartz (< 0.1%)	14808-60-7	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Cough; Lungs, Thorax, or Respiration:Dyspnea; Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Dyspnea; Inhalation-Bat TCLo • 15 mg/m³ 79 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Dyspnea; Multi-dose Toxicity: Inhalation-Rat TCLo • 15 mg/m³ 79 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosing alveolitis; Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Effect on inflammation or mediation of inflammation; Inhalation-Rat TCLo • 25 mg/m³ 5 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Sputum; Immunological Including Allergic:Increase in cellular immune response; Inhalation-Rat TCLo • 15 mg/m³ 79 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosing alveolitis; Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Effect on inflammation or mediation of inflammation; Inhalation-Rat TCLo • 25 mg/m³ 5 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Sputum; Immunological Including Allergic:Increase in cellular immune response; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s) 71 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Liver:Tumors; Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s) 71 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Liver:Tumors		
Talc (< 2%)	14807-96-6	Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 18 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma; Endocrine:Tumors; Inhalation-Rat TCLo • 18 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma; Endocrine:Tumors		

GHS Properties	Classification
Acute toxicity	EU/CLP•NDA
	OSHA HCS 2012•NDA
Aspiration Hazard	EU/CLP•NDA
Aspiration Hazard	OSHA HCS 2012•NDA
Carcinogenicity	EU/CLP•NDA
Carcinogenicity	OSHA HCS 2012•NDA
Germ Cell Mutagenicity	EU/CLP•NDA
Germ Cell Mutagericity	OSHA HCS 2012•NDA
Skin corrosion/Irritation	EU/CLP•NDA
Skill collosion/ilitation	OSHA HCS 2012•NDA
Skin sensitization	EU/CLP•NDA
Skill Selisitization	OSHA HCS 2012•NDA
STOT-RE	EU/CLP•NDA
3101-KE	OSHA HCS 2012•NDA
STOT-SE	EU/CLP•NDA
3101-3E	OSHA HCS 2012•NDA
Toxicity for Reproduction	EU/CLP•NDA
Toxicity for Reproduction	OSHA HCS 2012•NDA
Respiratory sensitization	EU/CLP•NDA
Nespiratory sensitization	OSHA HCS 2012•NDA
	EU/CLP•NDA
Serious eye damage/Irritation	OSHA HCS 2012•NDA
	GOTA TIGG ZOTZ NEW

Route(s) of entry/exposure Medical Conditions Aggravated by Exposure

- Inhalation, Skin, Eye, Ingestion
- Disorders of the lungs.

Potential Health Effects

Inhalation

Acute (Immediate)

 Exposure to dust may cause irritation. Processes such as cutting, grinding, crushing, or impact may result in generation of excessive amounts of airborne dusts in the workplace. Nuisance dust may affect the lungs but reactions are typically reversible.

Chronic (Delayed)

• Prolonged exposure to the dust may cause wheezing, chest tightness, productive cough nasal irritation and symptoms of chronic respiratory disease.

Skin

Acute (Immediate)

Exposure to dust may cause mechanical irritation.

Chronic (Delayed)

· No data available.

Eye

Acute (Immediate)

 Exposure to dust may cause mechanical irritation. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

No data available

Carcinogenic Effects				
	CAS IARC NTP			
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen	
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed	

Key to abbreviations

LD = Lethal Dose

MLD = Mild

Section 12 - Ecological Information

12.1 Toxicity

NDA

12.2 Persistence and degradability

NDA

12.3 Bioaccumulative potential

NDA

12.4 Mobility in Soil

NDA

12.5 Results of PBT and vPvB assessment

• PBT and vPvB assessment has not been carried out.

12.6 Other adverse effects

NDA

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not regulated	NDA	NDA	NDA
TDG	NDA	Not regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not regulated	NDA	NDA	NDA

14.6 Special precautions for user

- None known.
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
- Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

None

Inventories

These products comply with the following inventories:

Australia AICS Canada DSL/NDSL China EU EINECS/ ELNICS

Japan ENCS Korea KECI New Zealand Philippines PICCS

USA TSCA

California Prop 65

• In compliance, no reportable substances

CERCLA

• In the event of a spill, the end user should verify whether reporting is required

under local, state, and/or federal regulations.

CONEG

 These products are in compliance with the heavy metals requirements of the Coalition of Northeastern Governors and California Toxics in Packaging Prevention Act (AB2021).

Ozone Depleting Substances

• In compliance with 40 CFR 82, no reportable substances.

RCRA

 In the form delivered by Westlake, these products are not considered as hazardous waste, and are not subject to reporting under the Resource Conservation and Recovery Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date 07/January/2016

Preparation Date 12/December/2014

For Other Information Contact Westlake Polymers LLC Customer Service 1-800-545-9577

(Monday-Friday, 7:30am-5:00pm - central standard time)

Disclaimer/Statement of Liability

It is your responsibility to determine that our product is safe, lawful, and technically suitable for your intended uses. This safety data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of the user's operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this safety data sheet should be provided to employees and/or customers. Westlake Polymers LLC must rely on the user to use this information to develop appropriate work practice guidelines and employee instructional programs specific to the user's operation.

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of these products. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without warranty, expressed, or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable international, federal, state, and local laws and regulations regarding the use, storage, sale, transport or disposal of this material is the responsibility of the user.

Westlake Polymers LLC does not endorse or claim suitability of its product for any particular use. WESTLAKE MAKES NO WARRANTY OF MERCHANTABILITY AS TO ITS LDPE RESIN PRODUCTS. WESTLAKE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OR FITNESS OF ANY WESTLAKE PRODUCT FOR ANY PARTICULAR USE. Westlake's liability and your exclusive remedy for any claim arising out of the sales of its products are expressly limited at Westlake's option to replacement of non-performing goods or payment not to exceed the purchase price plus transportation charges thereon in respect to any material which damage is proven and claimed.

The information in this sheet is valid for cited regulations published as of the date this document was prepared, as shown herein. Updates may be prepared as the regulations are amended or pending revised information about the resin. It is the customer's responsibility to seek updated regulatory information on any specific resin.

Key to abbreviations NDA = No data available