



# Westlake Chemical

Westlake PVC Corporation  
a Westlake company  
2801 Post Oak Blvd.  
Houston, TX 77056

Phone: (800) 822-7529

Fax: (225) 685-1324

## 1070

This is a low molecular weight film and medical grade vinyl suspension resin. PVC-1070 is designed for clear and opaque extruded sheet, bottles, and other injection and blow molding applications. Kosher approved.

Item	Test Method	Typical Properties
ASTM Cell Classification	ASTM D1755	GP2-16340
Inherent Viscosity	PPVC 45A	0.69 +/- 0.02
Relative Viscosity		1.87
"K" Value	DIN 53726	57
Bulk Density, lbs/ft <sup>3</sup>	PPVC 24	>33.0
gms/cm <sup>3</sup>		>0.528
Volatiles, %	PPVC 22	<0.35
Syntron Contamination, Particles/100 gms	PPVC 35	<50
Residual Vinyl Chloride Monomer, ppm	PPVC 27	<1.0
HunterLab Color, 'L'	PPVC 38	>95.0
'a'		<0.9
'b'		<2.0
Particle Size Distribution	PPVC 31A	
Percent retained on 40 mesh		0
60 mesh		<5
200 mesh		<35
Pan		<7

Approved 10.28.2013 Rev. 6

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. These values and sets of properties are based upon laboratory work with small scale equipment and do not necessarily indicate end product performance. Full scale testing and end product use and performance are the responsibility of the Buyer. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents. "Value" may not be construed as product specifications.