



WESTLAKE PVC

Westlake Chemical Corp.
2801 Post Oak Blvd.
Houston, TX 77056
1-800-822-7529 or
225-685-2900

5265

Westlake 5265 is a low molecular weight, general purpose, vinyl suspension resin. Designed for clear and opaque applications. This resin has good clarity, color and thermal stability.

Suggested Applications

Westlake 5265 PVC resin is well suited for extruded sheet, bottles, fittings and other high flow, injection and blow molding applications.

TYPICAL PROPERTIES

Appearance (Visual Observation)	Free Flowing White Powder
K-value (ISO1628-2)	57
Inherent Viscosity (ASTM D5225)	0.68
Volatiles (%) (maximum)	0.35
Bulk Density (g/cc) (ASTM D1895)	0.51
Particle Size (ASTM D1921)	
Through 40 mesh (% minimum)	99.9
Through 200 mesh (% maximum)	6.0
ASTM Cell Classification (ASTM D1755)	GP1-16350

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.

Rev.01/19