



WESTLAKE PVC

Westlake Chemical Corp.
2801 Post Oak Blvd.
Houston, TX 77056
1-800-822-7529 or
225-685-2900

5395

Westlake 5395 is a medium molecular weight, general purpose, vinyl suspension resin. This resin has good clarity, color, plasticizer sorption and thermal stability.

Suggested Applications

Westlake 5395 PVC resin is well suited for flexible profile extrusion, extruded and calendered sheet, blown film, wire and cable, and other flexible applications.

TYPICAL PROPERTIES

| | |
|--|---------------------------|
| Appearance (Visual Observation) | Free Flowing White Powder |
| K-value (ISO1628-2) | 68 |
| Inherent Viscosity (ASTM D5225) | 0.95 |
| Volatiles (%) (maximum) | 0.35 |
| Bulk Density (g/cc) (ASTM D1895) | 0.48 |
| Particle Size (ASTM D1921) | |
| Through 40 mesh (% minimum) | 99.9 |
| Through 200 mesh (% maximum) | 5.0 |
| ASTM Cell Classification (ASTM D1755) | GP4-15560 |

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.

Rev.01/19